

WHAT IS CLAIMED IS:

1. A method for handover execution in a wireless environment, comprising:

communicating, by a mobile network, a handover
5 command message to a physical layer of a mobile station
to initiate a handover execution, the handover command
message being received by the physical layer and the
physical layer responding to the handover command message
by tuning to a handed to frequency and by communicating
10 physical layer bursts over the handed to frequency to the
mobile network such that initial timing advance and power
control setting characteristics are determined by the
mobile network; and

communicating a cease signal, by the mobile network,
15 to the mobile station to stop communicating the physical
layer bursts, the mobile station responding to the cease
signal by ending the transmission of the physical layer
bursts and by establishing a new communications link over
the handed to frequency with the mobile network, wherein
20 once the new communications link is established the
mobile station and the mobile network couple to a voice
path such that a wireless communication associated with
the mobile station and the mobile network is facilitated.

25 2. The method of Claim 1, wherein communicating
the handover command message to initiate the handover
execution to the physical layer comprises communicating
the handover command message through a radio resource
management (RRM) layer, a data link layer, and a physical
30 layer associated with the mobile network.

3. The method of Claim 2, further comprising
suspending signaling of a non-handover status, by the
physical layer of the mobile station, in response to the
handover command message that is communicated by the
5 mobile network.

4. The method of Claim 1, further comprising
completing a handover decision associated with the mobile
station and the mobile network before the handover
10 command message is communicated by the mobile network.

5. The method of Claim 1, wherein once the new
communications link is established between the mobile
station and the mobile network, the mobile station
15 communicates a signal to the mobile network indicating
completion of the handover execution.

6. A method for handover execution in a wireless environment, comprising:

receiving, from a mobile network, a handover command message to initiate a handover execution, the handover
5 command message being received by a physical layer of a mobile station;

tuning, by the physical layer, to a handed to frequency;

communicating, by the physical layer, physical layer
10 bursts over the handed to frequency to the mobile network such that initial timing advance and power control setting characteristics are determined by the mobile network;

receiving, from the mobile network, a cease signal
15 indicating to stop communicating the physical layer bursts;

ending, by the physical layer, the transmission of the physical layer bursts; and

establishing a new communications link over the
20 handed to frequency with the mobile network, wherein once the new communications link is established the mobile station and the mobile network couple to a data path such that a wireless communication associated with the mobile station and the mobile network is facilitated.

25

7. The method of Claim 6, wherein the handover command message to initiate the handover execution is communicated through a radio resource management (RRM) layer, a data link layer, and a physical layer associated
30 with the mobile network.

8. The method of Claim 7, further comprising suspending signaling of a non-handover status, by the physical layer of the mobile station, in response to the handover command message.

5

9. The method of Claim 6, further comprising completing a handover decision associated with the mobile station and the mobile network before the handover command message is received by the physical layer of the mobile station.

10

10. The method of Claim 6, wherein once the new communications link is established between the mobile station and the mobile network, the mobile station communicates a signal to the mobile network indicating completion of the handover execution.

15

11. Software embodied in a computer readable media for performing handover execution in a wireless environment, the software operable to:

communicate a handover command message to a physical
5 layer of a mobile station to initiate a handover execution, the handover command message being received by the physical layer of the mobile station and the physical layer responding to the handover command message by tuning to a handed to frequency and by communicating
10 physical layer bursts over the handed to frequency to a mobile network such that initial timing advance and power control setting characteristics are determined by the mobile network; and

communicate a cease signal to the mobile station to
15 stop communicating the physical layer bursts, the mobile station responding to the cease signal by ending the transmission of the physical layer bursts and by establishing a new communications link over the handed to frequency with the mobile network, wherein once the new
20 communications link is established the mobile station and the mobile network couple to a data path such that a wireless communication associated with the mobile station and the mobile network is facilitated.

25 12. The software of Claim 11, wherein the software that is operable to communicate the handover command message to initiate the handover execution to the physical layer of the mobile station comprises a radio resource management (RRM) layer, a data link layer, and a
30 physical layer associated with the mobile network.

13. The software of Claim 12, further operable to suspend signaling of a non-handover status, by the physical layer of the mobile station in response to the handover command message.

5

14. The software of Claim 11, further operable to complete a handover decision associated with the mobile station and the mobile network before the handover command message is communicated by the mobile network.

10

15. The software of Claim 11, wherein the mobile station comprises software operable to communicate a signal to the mobile network indicating completion of the handover execution after the new communications link is established between the mobile station and the mobile network.

15

16. Software embodied in a computer readable media for performing handover execution in a wireless environment, the software operable to:

receive, from a mobile network, a handover command
5 message to initiate a handover execution, the handover command message being received by a physical layer of a mobile station;

tune to a handed to frequency;

communicate physical layer bursts to the mobile
10 network over the handed to frequency such that initial timing advance and power control setting characteristics are determined by the mobile network;

receive, from the mobile network, a cease signal
15 indicating to stop communicating the physical layer bursts;

end the transmission of the physical layer bursts;
and

establish a new communications link with the mobile
network, wherein once the new communications link is
20 established the mobile station and the mobile network couple to a data path such that a wireless communication associated with the mobile station and the mobile network is facilitated.

25 17. The software of Claim 16, wherein the software operable to receive the handover command message to initiate the handover execution is in response to a communication from the mobile network, and wherein the software is further operable to communicate the handover
30 command message through a radio resource management (RRM) layer, a data link layer, and a physical layer associated with the mobile network.

18. The software of Claim 17, further operable to suspend signaling of a non-handover status in response to the handover command message that is received by the physical layer of the mobile station.

19. The software of Claim 16, further operable to complete a handover decision associated with the mobile station and the mobile network before the handover command message is received by the physical layer of the mobile station.

20. The software of Claim 16, wherein the mobile station comprises software operable to communicate a signal to the mobile network indicating completion of the handover execution after the new communications link is established between the mobile station and the mobile network.

21. A system for handover execution in a wireless environment, comprising:

means for communicating, by a mobile network, a handover command message to a physical layer of a mobile station to initiate a handover execution, the handover command message being received by the physical layer and the physical layer responding to the handover command message by tuning to a handed to frequency and by communicating physical layer bursts over the handed to frequency to the mobile network such that initial timing advance and power control setting characteristics are determined by the mobile network; and

means for communicating a cease signal, by the mobile network, to the mobile station to stop communicating the physical layer bursts, the mobile station responding to the cease signal by ending the transmission of the physical layer bursts and by establishing a new communications link over the handed to frequency with the mobile network, wherein once the new communications link is established the mobile station and the mobile network couple to a voice path such that a wireless communication associated with the mobile station and the mobile network is facilitated.

22. The system of Claim 21, wherein the means for communicating the handover command message to initiate the handover execution to the physical layer comprises means for communicating the handover command message through a radio resource management (RRM) layer, a data link layer, and a physical layer associated with the mobile network.

23. The system of Claim 22, further comprising
means for suspending signaling of a non-handover status,
by the physical layer of the mobile station, in response
to the handover command message that is communicated by
5 the mobile network.

24. The system of Claim 21, further comprising
means for completing a handover decision associated with
the mobile station and the mobile network before the
10 handover command message is communicated by the mobile
network.

25. The system of Claim 21, wherein once the new
communications link is established between the mobile
15 station and the mobile network, the mobile station
communicates a signal to the mobile network indicating
completion of the handover execution.

26. A system for handover execution in a wireless environment, comprising:

means for receiving, from a mobile network, a handover command message to initiate a handover execution, the handover command message being received by a physical layer of a mobile station;

means for tuning, by the physical layer, to a handed to frequency;

means for communicating, by the physical layer, physical layer bursts over the handed to frequency to the mobile network such that initial timing advance and power control setting characteristics are determined by the mobile network;

means for receiving, from the mobile network, a cease signal indicating to stop communicating the physical layer bursts;

means for ending, by the physical layer, the transmission of the physical layer bursts; and

means for establishing a new communications link over the handed to frequency with the mobile network, wherein once the new communications link is established the mobile station and the mobile network couple to a data path such that a wireless communication associated with the mobile station and the mobile network is facilitated.

27. The system of Claim 26, wherein the handover command message to initiate the handover execution is communicated through a radio resource management (RRM) layer, a data link layer, and a physical layer associated with the mobile network.

28. The system of Claim 27, further comprising means for suspending signaling of a non-handover status, by the physical layer of the mobile station, in response to the handover command message.

5

29. The system of Claim 26, further comprising means for completing a handover decision associated with the mobile station and the mobile network before the handover command message is received by the physical layer of the mobile station.

10

30. The system of Claim 26, wherein once the new communications link is established between the mobile station and the mobile network, the mobile station communicates a signal to the mobile network indicating completion of the handover execution.

15